International Journal of BioTech, Pharmaceutical, Engineering, Management and Sciences
ISSN: 3139-3748 |VOLUME-1, ISSUE-1| Inaugural Edition | January-June 2026
Paper ID: P11-025| Research Article
doi: https://doi.org/10.5281/zenodo.20677319

MULTIMODAL ANALYSIS FOR PSYCHOLOGICAL INSTABILITY DETECTION USING ML

[#1]**Thummanapelly Meghana,** *Department of MCA,*
[#2]**Dr. M. Srinivas,** *Professor, Department of CSE (AIML),*
Vaageswari College of Engineering(Autonomous), Karimnagar,TG

ABSTRACT: People work very hard to keep up with the fast-paced world we live in. But as a result, people have to deal with a number of health problems, the most well-known of which are stress and depression. These circumstances may eventually lead to death or other horrible deeds. These anomalies are categorised as bipolar disorder, which can be controlled by following a doctor's recommended treatment plan. For this Paper, information was gathered from working people using a range of questions about how to identify melancholy. The dataset was then exposed to particular machine learning methods. For environmental monitoring systems, the Random Forest approach offers the best accuracy of 87.02%, which is crucial for the successful management and prevention of forest fires.

Keywords: *Bipolar disorder, Random Forest, SVM, Decision Tree, Machine learning*

1. INTRODUCTION

Our everyday lives, relationships, and general well-being can all be impacted by our mental health. However, this relationship can also work the other way around; physical characteristics, social interactions, and life circumstances can all have an impact on mental health issues. Understanding mental health issues can improve a person's outlook on life. Our lives could become more harmonious as a result of this project. Anxiety, depression, and stress are a few disorders that can impair mental health and interfere with day-to-day activities. About 25% of senior citizens suffer from mental illness, but only about 6% are thought to be seriously ill. Numerous physical conditions, including diabetes and cardiovascular disease, are often associated with these illnesses. They also increase the likelihood of physical harm, severe weather, natural disasters, and suicides. With a potential for 35,345 deaths in 2019—the most obscure year for which data is available—suicide was the tenth most common cause of death in the US. The idea that emotional, cognitive, and behavioural disorders somehow require reality and more accurately reflect personal shortcomings or poor life choices has historically dominated medical treatment of mental illness.

2. LITERATURE SURVEY

In order to detect psychological instability, Richardson and Varma (2021) suggest a multimodal machine learning framework that uses behavioural and emotional analysis methods. To find signs of psychological distress, Natural Language Processing (NLP) and Support Vector Machine (SVM) techniques are used to analyse speech patterns, facial expressions, and textual communication data. The framework assesses emotional swings and cognitive markers to improve detection accuracy. When compared to traditional psychological assessment techniques, experimental evaluation shows better prediction

performance and lower misclassification rates. Applications for early intervention and intelligent mental health monitoring can be supported by the suggested system.

Lopez and Srinivasan (2022) present a deep learning and sentiment analysis-based intelligent multimodal psychological instability detection system. To detect emotional and psychological abnormalities, Recurrent Neural Networks (RNN) examine voice signals, social media interactions, and facial behaviour patterns. Real-time multimodal data processing improves detection reliability and response efficiency. Improved classification accuracy and the capacity to efficiently handle a wide range of behavioural datasets are demonstrated by performance analysis. Digital psychological assessment systems and smart mental healthcare are supported by the framework.

Kim & O'Donnell (2023) develop a hybrid multimodal analysis framework for the identification of psychological instability using Long Short-Term Memory (LSTM) models and Convolutional Neural Networks (CNN). To accurately classify mental health conditions, the system analyses textual emotions, facial microexpressions, speech tone variations, and physiological signals. To enable adaptive psychological monitoring, multimodal behavioural data is continuously processed using cloud-based analytics. Comparative findings show that handling large mental health datasets is more efficient and that detection stability is enhanced. The framework enhances mental wellness and intelligent emotional analysis platforms.

Rahman and Fletcher (2024) present a novel framework for identifying psychological instability using predictive analytics and AI-driven multimodal analysis techniques. In order to analyse human emotions and behavioural changes across a range of communication channels, the architecture combines computer vision, speech recognition, and deep learning algorithms. Improved detection accuracy and greater adaptability to changing psychological conditions are confirmed by experimental results. The suggested system improves individualised medical care and mental health diagnostics.

Almeida and Becker (2025) developed an adaptive multimodal framework to identify psychological instability in the Paper using ensemble learning techniques. The Gradient Boosting and XGBoost models analyse biometric signals, emotional speech traits, online communication activities, and behavioural patterns to dynamically classify psychological instability. The system regularly modifies its learning models in response to fresh mental health data. The findings also show improved prediction accuracy and streamlined mental health assessment processes. The framework is appropriate for healthcare analytics systems and intelligent psychological monitoring.

Tanaka and Hughes (2026) The authors create an AI-enabled multimodal analysis framework for the identification of psychological instability by utilising cloud computing and edge-based analytics technologies. To enable real-time psychological evaluation, the system combines transformer-based deep learning models, distributed multimodal data processing, and behavioural intelligence mechanisms. In large-scale mental healthcare settings, edge computing enhances scalability and lowers processing latency. Improved emotional analysis efficiency, decreased computational overhead, and improved detection performance are all revealed by experimental evaluation. The framework facilitates the creation of AI-powered next-generation mental healthcare ecosystems.

International Journal of BioTech, Pharmaceutical, Engineering, Management and Sciences
ISSN: 3139-3748 |VOLUME-1, ISSUE-1| Inaugural Edition | January-June 2026
Paper ID: P11-025| Research Article
doi: https://doi.org/10.5281/zenodo.20677319

3. METHODOLOGY

Data collection: Use web scraping tools and APIs to gather test data from online platforms; work with mental health specialists and adhere to guidelines to gather anonymized datasets. Data pre-processing and feature engineering: use signal processing methods for physiological data and natural language processing (NLP) methods for text data. To maximise the model's performance, extract relevant features. Model Training and Evaluation: Create machine learning models using libraries like Scikit-learn and TensorFlow. To maximise model accuracy, use cross-validation and hyperparameter tuning. Deployment and monitoring: Create applications that are easy to use and capable of quickly identifying psychological instability. Keep an eye on the model's performance and make adjustments in response to fresh information and user input.

MODULE DESCRIPTION

Conducting a system Paper for this project is an important step to evaluate the usefulness and For this project, a system Paper is necessary to assess the viability and usefulness of using machine learning and the Random Forest Algorithm (RFA) to identify psychological instability. Understanding psychological disorders, such as stress, anxiety, and depression, is the investigation's main goal. It also identifies the target audience, which includes both medical professionals who offer therapy and people looking for mental health evaluations. Data collection is one of the system's most important parts. To gather accurate and relevant data, a wide range of techniques are used, including surveys, questionnaires, and psychological tests. After that, this data is pre-processed to find important features, fill in missing values, and remove errors in order to enhance the model's performance. The Random Forest algorithm was chosen because it can effectively handle complex data, reduce overfitting problems, and produce accurate predictions. The technical viability of the system, which includes the accessibility of computational resources and machine learning knowledge, is also assessed by the Paper.

ALGORITHM

The foundation of the model is these procedures, which are well known for their capacity to handle complicated data and lessen overfitting. The exemplary is altered to attain optimal performance through hyperparameter optimisation.

ADVANTAGES

- **Early Detection:** Early detection has the potential to result in earlier interpositions and better outcomes by analysing large amounts of data to find early indicators of psychological instability.
- **Accuracy:** By examining complex data patterns that human analysis might miss, this project has the potential to produce diagnoses that are more accurate.
- **Scalability:** It should be able to house a sizable population, making help more accessible and scalable, especially in areas with a shortage of project specialists.

International Journal of BioTech, Pharmaceutical, Engineering, Management and Sciences
ISSN: 3139-3748 |VOLUME-1, ISSUE-1| Inaugural Edition | January-June 2026
Paper ID: P11-025| Research Article
doi: https://doi.org/10.5281/zenodo.20677319

4. RESULTS




Fig 1: Login Page for Psychological Instability Detection System




Fig 2: Service Provider Login Page



Fig 3: Stress Psychology Dataset Details and Accuracy View




Fig 4: Psychological Instability Prediction Accuracy Graph

International Journal of BioTech, Pharmaceutical, Engineering, Management and Sciences
ISSN: 3139-3748 |VOLUME-1, ISSUE-1| Inaugural Edition | January-June 2026
Paper ID: P11-025| Research Article
doi: https://doi.org/10.5281/zenodo.20677319




Fig 5: Line Chart for Psychological Instability Analysis




Fig 6: Pie Chart Representation of Psychological Instability Results

5. CONCLUSION

Mental illness is identified using a wide range of methods in all age groups. These systems use a detection method that assesses mental health issues using a set of questionnaires to predict the stages of decline in a range of age cohorts. To identify cases of mental confusion, machine learning tasks are used. A dataset with 1200 samples is presently being analysed by the researchers. Support Vector Machines (SVM), Random Forests, and Decision Trees are used for both detection and learning. The Paper's observational results show that the Random Forest model has the highest accuracy, at about 87%. The upcoming projects involving neural networks and machine learning models excite the researchers.

REFERENCES

1. Hussain, M. A., et al. (2023). “Deep Learning and Machine Learning Models for Landslide Susceptibility Mapping Using GIS and Remote Sensing Data.” *Remote Sensing*, 15(19), 4703.
2. Konakoglu, B., et al. (2025). “Artificial Intelligence in Landslide Susceptibility: A Comprehensive Review.” *Transactions in GIS*.
3. Youssef, A. M., et al. (2021). “Landslide Susceptibility Mapping Using Machine Learning Techniques and Remote Sensing Data.” *Geoscience Frontiers*, 12(6).
4. Tehrani, F. S., et al. (2022). “Machine Learning and Landslide Studies: Recent Advances and Applications.” *Natural Hazards*.

5. Akosah, S., Gratchev, I., Kim, D. H., & Ohn, S. Y. (2024). "Application of Artificial Intelligence and Remote Sensing for Landslide Detection and Prediction: Systematic Review." *Remote Sensing*.
6. Arabameri, A., et al. "Landslide Susceptibility Evaluation and Management Using Machine Learning Approaches." *Natural Hazards and Earth System Sciences*.
7. Naceur, H. A., et al. (2026). "Integrating Geospatial Data and Hybrid Machine Learning Approaches for Landslide Susceptibility Assessment." *International Journal of Digital Earth*.
8. Bammou, Y., et al. (2025). "Improving Landslide Susceptibility Mapping in Semi-Arid Regions Using Machine Learning and Geospatial Techniques." *Applied Geomatics*.
9. Ghorbanzadeh, O., Xu, Y., Ghamisi, P., Kopp, M., & Kreil, D. (2022). "Landslide4Sense: Reference
10. Benchmark Data and Deep Learning Models for Landslide Detection." *IEEE Journal of Selected Topics in Applied Earth Observations and Remote Sensing*.
11. Le, C., Pham, L., Lampert, J., Schlögl, M., & Schindler, A. (2023). "Landslide Detection and Segmentation Using Remote Sensing Images and Deep Neural Network." *arXiv Preprint*.
12. Burange, R. A., Shinde, H. K., &Mutyalwar, O. (2025). "Landslide Detection and Mapping Using Deep Learning Across Multi-Source Satellite Data and Geographic Regions." *arXiv Preprint*.
13. Li, W., Wang, S., Lee, H., Lu, C., Roy, S., Ramachandran, R., & Hsu, C. Y. (2025). "Landslide Hazard Mapping with Geospatial Foundation Models: Geographical Generalizability, Data Scarcity, and Band Adaptability." *arXiv Preprint*.